by Raden Lukas Martindro Satrio Ari Wibowo

Submission date: 01-May-2023 10:36AM (UTC+0800)

Submission ID: 2080387365

File name: ISFA Manuscript ID AF-001-2021.doc (86K)

Word count: 1200 Character count: 6513

Raden Lukas Martindro Satrio Ari Wibowo¹, Tutik Maryati², and Ragil Yuliatmo^{1,2a)}

Laboratory of Microbiology and Enzyme, Politeknik ATK Yogyakarta, Special District of Yogyakarta, 55281, Indonesia.

²Laboratory of Beam House Operation and Tanning, Politeknik ATK Yogyakarta, Special District of Yogyakarta, 55281, Indonesia,

a) Corresponding author: ragilyuliatmo@atk.ac.id

Abstract. Rabbit skin as a by-product has potential value in producing fur skin for making hats, clothes, wall hangings, bags, upholstery for household furniture. Fatliquoring is one of the final operations of post tanning process that influenced the physical characteristics on fur leather. Egg yolk is suitable as fatliquoring agent because it contains a natural emulsifier (lecithin) which works as an emulsion stabilizer so that the fat can be penetrated into the collagen fibers perfectly. This study aims to determine the effect of utilize egg yolk as a fatliquoring agent in rabbit fur tanning. Egg yolk was used as a fatliquoring agent, with concentrations of 8, 10, and 12%. The concentration of egg yolk as a fatliquoring agent affected the physical properties of the rabbit fur leather. Increasing the concentration of egg yolk can increase the tensile strength, elongation, sewing strength, and tear strength significantly. This rabbit fur leather suitable to use as gloves

INTRODUCTION

Rabbits have the ability to reproduce and grow fast. Maintenance is simple and inexpensive and can be adapted for small and commercial scales¹. The products obtained from raising rabbits are meat and fur skin, as well as other parts, all of which are utilized through certain processing stages². Rabbit skin as a by-product has potential value in producing fur skin, with certain processing steps, the skin can be used as a leather product that can be used as raw material for making hats, clothes, wall hangings, bags, upholstery for household furniture³, scarves, seat covers, wallets, dolls and other high-priced leather crafts⁴.

Leather making technology consists of many phases which can be divided into processes of beamhouse, tanning, post tanning, and finishing. Fatliquoring is one of the final operations of post tanning process⁵. The fatliquors used in this phase influenced the physical characteristics of leather such as flexibility, feel, and stitch tear resistance⁶. The commonly used fatliquors are synthetic oils and natural oils such as fish oil and palm oil. The natural materials must be sulfonified to become fatliquoring agents. The sulfonation process can lead to environmental pollution as a result of the liquid waste from the tanning process. In addition, the sustainability of natural materials are determined by its abundance, existing usage.

In Indonesia, eggs are an abundant natural material, easy to find, cheap, and have a high fat content in egg yolks. Egg yolk contains a natural emulsifier (lecithin) which works as an emulsion stabilizer so that the fat can be penetrated into the collagen fibers perfectly, so that the tanned skin becomes weak and soft⁷. This study aims to determine the effect of utilize egg yolk as a fatliquoring agent in rabbit fur tanning.

MATERIAL AND METHODS

The materials used are local rabbit skin, egg yolk, and tanning materials. This research was conducted with an experimental method. Egg yolk was used as a fatliquoring agent, with concentrations of 8, 10, and 12%. The fatliquoring process is based on Nkwor & Ukoha⁶ method. The physical characteristic of leather was tested including tensile strength, elongation, sewing strength, and tear resistance⁸. The data obtained were analyzed by analysis of variance (ANOVA) using IBM SPSS Statistics 25.

RESULT AND DISCUSSION

The results of the physical properties of rabbit fur leather are shown in Table 1. Based on the results, it can be seen that the higher the concentration of the fatliquoring agent, the higher the physical properties of the fur significantly. Based on Indonesian national standards (SNI), this fur is not suitable for jackets, but can be used as gloves. Tensile strength of fur skin with fatliquoring agent 12% yielded 116.51 kg/cm². SNI 4593-20119 regarding leather jacket standards requires a minimum tensile strength of more than 141 kg/cm², while SNI 06-0237 regarding gloves standards requires a minimum of 75 kg/cm².

Fur skin with a concentration of 12% fatliquor agent produces an elongation percentage of 77.10%. This value is higher than the study by Yorgancioglu¹¹, which used 15% fatliquoring agent from tymol (58%). The same applies to the leather with the fatliquor agent from *Afzelia africana Aril Cap* Oil which has elongation properties of 40.42%⁶, 2020). The value of sewing strength on fur with fatlioring of egg yolk ranged from 50.21 kg/cm² to 58.65 kg/cm². Kanagy¹² stated that sewing strength is also influenced by skin thickness, collagen protein content and density, the angle of the bundle of collagen fibers, and the thickness of the corium.

TABLE 1. Physical characteristic of rabbit fur leather

Parameter.	Fatliquoring agent concentration (%)			
Parameter 6	8	10	12	
Tensile Strength (kg/cm ²)	84,89±6,18 ^a	98,62±5,26 ^b	116,51±7,40°	
Elongation (%)	68,47±1,66a	73,10±1,01 ^b	77,10±2,76°	
Sewing Strength (kg/cm)	50,21±2,82a	55,83±0,59b	58,65±0,77°	
Tear Resistance (kg/cm)	18.67±0.56 ^a	20.18±0.06 ^b	21.76±0.37°	

Results are given as mean ± standard deviation

Based on the results of the tear strength assay, the fur leather with 12% fatliquoring agent has a tear strength of 21.76 kg/cm. This value is lower than that of leather that has been fatliquified with natural ingredients such as flax (83.2 kg/cm) and soy (87.1 kg/cm)⁵. However, the value of the tear strength in this study was higher than that of Alfawal et al¹³, which used 12% fatliquoring agent from Jatropha oil (18,7 kg/cm).

CONCLUSION

The concentration of egg yolk as a fatliquoring agent affected the physical properties of the rabbit fur leather. Increasing the concentration of egg yolk can increase the tensile strength, elongation, sewing strength, and tear strength significantly. This rabbit fur leather suitable to use as gloves.

ACKNOWLEDGMENTS

The author would like to thank for funding given by research institutions and community service of Politeknik ATK Yogyakarta, and Indonesia Ministry of Industry for their facilities and support.

abc Different letters within the same row indicate statistical significance at p<0.05 level

REFERENCES

- W. Yu, X. M. Wang, L. Ma, H. J. Li, Z. F. He, and Y. H. Zhang, 2016. Int. J. Food Sci. Technol, 51(3), 574-580 (2016).
- M. Ma, L. Ma, W. Yu, X. Zhang, Y. Shen, and Y. Zhang. 2017. Food Hydrocolloids 77, 945-951 (2017)
- 3. T. Covington, Tanning Chemistry: The Science of Leather (RSC publishing, Northampton, UK, 2009)
- 4. P. S. Palupi, Kelinci rex penghasil kulit bulu (Pusat Informasi Pertanian Trubus, Jakarta, 1992)
- 5. J. Zarlok, K. Scmiechowski, K. Mucha, A. Tecza. J Cleaner Prod. 65, 583-589 (2014).
- A. N. Nkwor, P. O. Ukoha. Heliyon 6 (2020).
- 7. Mustakim. Jurnal Ilmu dan Teknologi Hasil Ternak 4 (2009).
- 8. R. L. M. S. A. Wibowo, E. Anggriyani, R. Yuliatmo, Leather Footwear J. 18 (2018).
- 9. BSN. Indonesian National Standard SNI 4593:2011: Leather Jacket (BSN, Jakarta, 2011).
- 10. BSN. Indonesian National Standard SNI 06-0237-1989: Leather Lining (BSN, Jakarta, 1980)
- 11. A. Yorgancioglu. J.Ind. Textiles. 0, 1-16 (2020)
- 12. J.R. Kanagy, "Physical and Performance Properties of Leather" in *The Chemistry and Technology of Leather* (Krieger Publishing Company. Florida, 1977)
- 13. G. S. Alfawal, Z. A. Nofal, A. E. Khattab, and A. I. Nasr. Egypt. J. of Appl. Sci., 35 (2020).

ORIGINALITY REPORT PUBLICATIONS SIMILARITY INDEX **INTERNET SOURCES** STUDENT PAPERS **PRIMARY SOURCES** revistapielarieincaltaminte.ro Internet Source vufind.katalog.k.utb.cz Internet Source Ricca Rahman Nasaruddin, Md. Zahangir Alam, Mohammed Saedi Jami. "Evaluation of solvent system for the enzymatic synthesis of ethanol-based biodiesel from sludge palm oil (SPO)", Bioresource Technology, 2014 Publication www.researchgate.net Internet Source Mohammad Furquan, S. Vijayalakshmi, Sagar 5 Mitra. "Iron oxide shell coating on nano silicon prepared from the sand for lithium-ion battery application", AIP Publishing, 2018 Publication Subramani Saravanabhavan, Palanisamy 6 Thanikaivelan, Jonnalagadda Raghava Rao,

Balachandran Unni Nair, Thirumalachari Ramasami. "Reversing the Conventional Leather Processing Sequence for Cleaner Leather Production", Environmental Science & Technology, 2006

Publication

Exclude quotes On

Exclude bibliography

Exclude matches

Off

PAGE 1			
PAGE 2			
PAGE 3			