by Raden Lukas Martindro Satrio Ari Wibowo

Submission date: 01-May-2023 10:50AM (UTC+0800)

Submission ID: 2080408626

File name: lization_of_egg_yolk_as_an_alternative_fatliquoring_agent_1.pdf (389.65K)

Word count: 1404 Character count: 7371

Cite as: AIP Conference Proceedings 2586, 040010 (2023); https://doi.org/10.1063/5.0110113 Published Online: 24 January 2023

Raden Lukas Martindro Satrio Ari Wibowo, Tutik Maryati and Ragil Yuliatmo





ARTICLES YOU MAY BE INTERESTED IN

Development of self nanoemulsifying drug delivery system (SNEDDS) to improve antioxidant activity of single garlic extract (Allium sativum L.)

AIP Conference Proceedings 2634, 020003 (2023); https://doi.org/10.1063/5.0111654

Sweet corn performance through organic farming approach

AIP Conference Proceedings 2586, 020003 (2023); https://doi.org/10.1063/5.0106345



APL Machine Learning

Machine Learning for Applied Physics Applied Physics for Machine Learning

Now Open for Submissions



AIP Conference Proceedings 2586, 040010 (2023); https://doi.org/10.1063/5.0110113 © 2023 Author(s).

Raden Lukas Martindro Satrio Ari Wibowo¹, Tutik Maryati², and Ragil Yuliatmo^{1,2a)}

¹ Laboratory of Microbiology and Enzyme, Politeknik ATK Yogyakarta, Special District of Yogyakarta, 55281, Indonesia.

²Laboratory of Beam House Operation and Tanning, Politeknik ATK Yogyakarta, Special District of Yogyakarta, 55281, Indonesia

a) Corresponding author: ragilyuliatmo@atk.ac.id

Abstract. Rabbit skin as a by-product has potential value in producing fur skin for making hats, clothes, wall hangings, bags, upholstery for household furniture. Fatliquoring is one of the final operations of post tanning process that influenced the physical characteristics on fur leather. Egg yolk is suitable as fatliquoring agent because it contains a natural emulsifier (lecithin) which works as an emulsion stabilizer so that the fat can be penetrated into the collagen fibers perfectly. This study aims to determine the effect of utilize egg yolk as a fatliquoring agent in rabbit fur tanning. Egg yolk was used as a fatliquoring agent, with concentrations of 8, 10, and 12%. The concentration of egg yolk as a fatliquoring agent affected the physical properties of the rabbit fur leather. Increasing the concentration of egg yolk can increase the tensile strength, elongation, sewing strength, and tear strength significantly. This rabbit fur leather suitable to use as gloves

INTRODUCTION

Rabbits have the ability to reproduce and grow fast. Maintenance is simple and inexpensive and can be adapted for small and commercial scales [1]. The products obtained from raising rabbits are meat and fur skin, as well as other parts, all of which are utilized through certain processing stages [2]. Rabbit skin as a by-product has potential value in producing fur skin, with certain processing steps, the skin can be used as a leather product that can be used as raw material for making hats, clothes, wall hangings, bags, upholstery for household furniture [3], scarves, seat covers, wallets, dolls and other high-priced leather crafts [4].

Leather making technology consists of many phases which can be divided into processes of beamhouse, tanning, post tanning, and finishing. Fatliquoring is one of the final operations of post tanning process [5]. The fatliquors used in this phase influenced the physical characteristics of leather such as flexibility, feel, and stitch tear resistance [6]. The commonly used fatliquors are synthetic oils and natural oils such as fish oil and palm oil. The natural materials must be sulfonified to become fatliquoring agents. The sulfonation process can lead to environmental pollution as a result of the liquid waste from the tanning process. In addition, the sustainability of natural materials are determined by its abundance, existing usage.

In Indonesia, eggs are an abundant natural material, easy to find, cheap, and have a high fat content in egg yolks. Egg yolk contains a natural emulsifier (lecithin) which works as an emulsion stabilizer so that the fat can be penetrated into the collagen fibers perfectly, so that the tanned skin becomes weak and soft [7]. This study aims to determine the effect of utilize egg yolk as a fatliquoring agent in rabbit fur tanning.

MATERIAL AND METHODS

The materials used are local rabbit skin, egg yolk, and tanning materials. This research was conducted with an experimental method. Egg yolk was used as a fatliquoring agent, with concentrations of 8, 10, and 12%. The fatliquoring process is based on Nkwor & Ukoha [7] method. The physical characteristic of leather was tested including tensile strength, elongation, sewing strength, and tear resistance [8]. The data obtained were analyzed by analysis of variance (ANOVA) using IBM SPSS Statistics 25.

RESULT AND DISCUSSION

Based on the results in table I, it can be seen that the higher the concentration of the fatliquoring agent, the higher the physical properties of the fur significantly. Based on Indonesian national standards (SNI), this fur is not suitable for jackets, but can be used as gloves. Tensile strength of fur skin with fatliquoring agent 12% yielded 116.51 kg/cm². SNI 4593-2011 [9] regarding leather jacket standards requires a minimum tensile strength of more than 141 kg/cm², while SNI 06-0237 [10] regarding gloves standards requires a minimum of 75 kg/cm².

Fur skin with a concentration of 12% fatliquor agent produces an elongation percentage of 77.10%. This value is higher than the study by Yorgancioglu [11], which used 15% fatliquoring agent from tymol (58%). The same applies to the leather with the fatliquor agent from *Afzelia africana Aril Cap* Oil which has elongation properties of 40.42%. The value of sewing strength on fur with fatlioring of egg yolk ranged from 50.21 kg/cm² to 58.65 kg/cm². Kanagy [12] stated that sewing strength is also influenced by skin thickness, collagen protein content and density, the angle of the bundle of collagen fibers, and the thickness of the corium.

TABLE 1. Physical characteristic of rabbit fur leather

Parameter -	Fa	tliquoring agent concentration	(%)
11	8	10	12
Tensile Strength (kg/cm ²)	84,89±6,18 ^a	98,62±5,26 ^b	116,51±7,40°
Elongation (%)	$68,47\pm1,66^{a}$	$73,10\pm1,01^{b}$	$77,10\pm2,76^{c}$
Sewing Strength (kg/cm)	$50,21\pm2,82^{a}$	55,83±0,59 ^b	$58,65\pm0,77^{\circ}$
Tear Resistance (kg/cm)	18.67 ± 0.56^{a}	20.18 ± 0.06^{b}	$21.76\pm0.37^{\circ}$

Results are given as mean \pm standard deviation

Based on the results of the tear strength assay, the fur leather with 12% fatliquoring agent has a tear strength of 21.76 kg/cm. This value is lower than that of leather that has been fatliquified with natural ingredients such as flax (83.2 kg/cm) and soy (87.1 kg/cm) [5]. However, the value of the tear strength in this study was higher than that of Alfawal et al [13], which used 12% fatliquoring agent from Jatropha oil (18,7 kg/cm).

CONCLUSION

The concentration of egg yolk as a fatliquoring agent affected the physical properties of the rabbit fur leather. Increasing the concentration of egg yolk can increase the tensile strength, elongation, sewing strength, and tear strength significantly. This rabbit fur leather suitable to use as gloves.

ACKNOWLEDGMENTS

The author would like to thank for funding given by research institutions and community service of Politeknik ATK Yogyakarta, and Indonesia Ministry of Industry for their facilities and support.

REFERENCES

- W. Yu, X. M. Wang, L. Ma, H. J. Li, Z. F. He, and Y. H. Zhang, Int. J. Food Sci. Technol, 51, 574-580 (2016).
- 2. M. Ma, L. Ma, W. Yu, X. Zhang, Y. Shen and Y. Zhang, Food Hydrocolloids 77, 945-951 (2017).
- 3. T. Covington, Tanning Chemistry: The Science of Leather (RSC publishing. Northampton, UK, 2009)

abc Different letters within the same row indicate statistical significance at p<0.05 level

- 4. P. S. Palupi, Kelinci rex penghasil kulit bulu (Pusat Informasi Pertanian Trubus, Jakarta, 1992)
- 5. J. Zarlok, K. Scmiechowski, K. Mucha and A. Tecza, J Cleaner Prod. 65, 583-589 (2014).
- 6. N. Nkwor and P. O. Ukoha. Heliyon 6 (2020).
- 7. Mustakim, J. Ilmu dan Teknologi Hasil Ternak 4 (2009).
- 8. R. L. M. S. A. Wibowo, E. Anggriyani and R. Yuliatmo, Leather Footwear J. 18 (2018).
- 9. BSN. Indonesian National Standard SNI 4593:2011: Leather Jacket (BSN, Jakarta, 2011).
- 10. BSN. Indonesian National Standard SNI 06-0237-1989: Leather Lining (BSN, Jakarta, 1980)
- 11. A. Yorgancioglu. J.Ind. Textiles. 0, 1-16 (2020)
- 12. J.R. Kanagy, "Physical and Performance Properties of Leather" in *The Chemistry and Technology of Leather* (Krieger Publishing Company. Florida, 1977)
- 13. G. S. Alfawal, Z. A. Nofal, A. E. Khattab and A. I. Nasr, Egypt. J. of Appl. Sci., 35 (2020).

ORIGINALITY REPORT

18% SIMILARITY INDEX

13%
INTERNET SOURCES

16%
PUBLICATIONS

5% STUDENT PAPERS

PRIMARY SOURCES

Sri Rahayu Lestari, Nenes Prastita, Siti Imroatul Maslikah, Sunaryono et al. "Development of self nanoemulsifying drug delivery system (SNEDDS) to improve antioxidant activity of single garlic extract (Allium sativum L.)", AIP Publishing, 2023

3%

Tanalyna Hasna, Sri Mulyani, Umar Santoso, Yudi Pranoto. "Physical and chemical properties of Buffalo skin gelatin extracted using crude acid protease from goat abomasum", AIP Publishing, 2023

2%

Iwan Fajar Pahlawan, Endang Purbowati, Sri Mulyani, Retno Adiwinarti, Agung Purnomoadi, Edy Rianto, Vita Restitrisnani. "The evaluation on the quality of lambskin leather originated from lambs fed by different feedstuffs", AIP Publishing, 2023

7%

Publication

4	irep.iium.edu.my Internet Source	2%
5	vufind.katalog.k.utb.cz Internet Source	2%
6	coek.info Internet Source	1 %
7	www.ncbi.nlm.nih.gov Internet Source	1 %
8	Submitted to Universitas Negeri Jakarta Student Paper	1 %
9	www.ejurnal-analiskesehatan.web.id	1 %
10	eprints.lancs.ac.uk Internet Source	1 %
11	Subramani Saravanabhavan, Palanisamy Thanikaivelan, Jonnalagadda Raghava Rao, Balachandran Unni Nair, Thirumalachari Ramasami. "Reversing the Conventional Leather Processing Sequence for Cleaner Leather Production", Environmental Science & Technology, 2006 Publication	1 %
	Arief Sudarmaji Agus Margiwiyatno Susanto	1

Arief Sudarmaji, Agus Margiwiyatno, Susanto Budi Sulistyo. "Characteristics of array MOS gas sensors in detection of adulteration on

%

patchouli oil with candlenut oil", AIP Publishing, 2023

Publication

Ji Lang, Rungun Nathan, Qianhong Wu. "How 1 % 13 to deform an egg yolk? On the study of soft matter deformation in a liquid environment", Physics of Fluids, 2021 Publication Yugi R. Ahadiyat, Okti Herliana, Ahmad Fauzi. 1 % "Sweet corn performance through organic farming approach", AIP Publishing, 2023 **Publication** "Committees: 3rd International Symposium <1% on Food and Agrobiodiversity (The 3rd ISFA)", AIP Publishing, 2023

Exclude quotes On Exclude bibliography On

Publication

Exclude matches

Off

F	PAGE 1				
F	PAGE 2				
F	PAGE 3				
F	PAGE 4				